	DECLARATION OF PERFORMANCE	Number	48/2019
		Date of issue	09.01.2019
		Page 1 of 2	

1. Unique identification code of the product-type:

The three-layer membrane for waterproofing and damp AlphaProPlus

2. Intended use/es:

Plastic or rubber sheet used on or under floors/ground slabs or in walls to prevent liquid water not under hydrostatic pressure passing from the ground into the internal environment
 Sheet used in wall construction or in or under floors or ground slabs to prevent liquid water under hydrostatic pressure passing from the ground into the internal environment or from one section of the structure to another.

3. Manufacturer:

Address: **Alpha Dam Sp. z o.o.**
Dębowa Łąka 45
87-207 Dębowa Łąka 45

4. System/s of AVCP

System 2+

5. Harmonised standard:


PN-EN 13967: 2012 Flexible sheets for waterproofing – Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet – Definitions and characteristics

Notified body/ies: **1434, 1488**

Certification body/ies: **1023**

Institut pro testovani a certifikaci a.s., T. Bati 299, 764 21 Zlin, Czechy

Conducted an inspection of factory and factory production control and inspection surveillance assessment and evaluation on factory production control system 2+ and issued Certificate of Conformity of the Factory Production Control No 1023-CPR-0446 F for AlphaProPlus

	DECLARATION OF PERFORMANCE	Number	48/2019
		Date of issue	09.01.2019
		Page 2 of 2	

6. Declared performance/s:

Essential characteristic	Unit	Performance
Reaction on fire	class	E
Watertightness	60 kPa Method B	Watertight
Tear resistance: - in transverse direction: - in longitudinal direction:	N N	≥ 400 ≥ 450
Joint strength	N	≥ 400
Resistance to impact	mm Method A	≥ 450
Tensile properties: Maximum strength: - in longitudinal direction: - in transverse direction: Elongation: - in longitudinal direction: - in transverse direction	N/50mm N/50mm % %	≥ 500 ≥ 400 ≥ 400 ≥ 100
Resistance to static loading	kg Method B	≥ 20
Durability - watertightness after artificial ageing - alkali resistance	60 kPa method B	Watertight no cracks and holes
Dangerous substance	-	don't contain

7. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Proxy Iwona Majek
Dębowa Łąka, 9 January 2019