

1. Unique identification code of the product-type:

Membrane of the elastomer for horizontal damp insulation of buildings AlphaHP Ultra

2. Intended use/es:

The purpose of damp proof courses is to prevent water rising up a wall from ground, water moving from one part of a wall to another and to deflect water from an inner wall of a cavity wall construction to the exterior of the building

3. Manufacturer:

Address: Alpha Dam Sp. z o.o.  
Dębowa Łąka 45  
87-207 Dębowa Łąka 45

4. Systems/s of AVCP:

System 3

5. Harmonised standard:

PN-EN 14909:2012 Flexible sheets for waterproofing – Plastic and rubber damp proof courses – Definitions and characteristics


Notified body/ies: 1434, 1488

6. Declared performance/s:

Essential characteristics	Unit	Performance	
		0,750	1,100
Watertightness	2 kPa Method A	Watertight	Watertight
Resistance to impact	mm Method A	≥ 2000	≥ 2000
Durability - watertightness after artificial ageing - alkali resistance	2 kPa Method A 2 kPa method A	Watertight no cracks and holes	Watertight no cracks and holes
Resistance to low temperature	°C	≤ -30	≤ -30
Reaction to fire	class	E	E
Dangerous substance	-	don't contain	don't contain

7. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Proxy Iwona Majek

Dębowa Łąka, 8 June 2016